

PRESSIZA 06

PERFORMANCE GUIDE



Features

- Ultrasmooth coated facestock which provides premium barcode printing for high and medium speed printers
- Versatile, general purpose permanent adhesive designed for excellent adhesion to corrugated cardboard and superior adhesion to plastics
- Excellent initial tack without sacrificing high speed converting. For use with all information printing technologies, including laser
- Bleached super calendered kraft stock featuring high internal strength, toughness, and tear resistance. Used primarily for roll-to-roll label applications

Face

Caliper 0.0030 +/- 10% inches

Adhesive

Thickness 0.0007 +/- 10% inches

Peel Adhesion Glass: 1.9 lbs

Temperature Ranges

Minimum Application +38°F (+3°C)

Service Ranges -65° F to +200° F (-54°C to 93°C)

Liner

Caliper 0.0024 +/- 10% inches

Basis Weight 40 +/- 10%
(24" x 36" 500 sheets)

Shelf Life

Unless otherwise specified in this document, ideally store at 72°F and 50% RH

Suggested applications

This product is suitable for use in applications where high quality barcode printing is critical.

Important:

Meets the requirements of FDA CFR 175.105 for indirect food contact. Compliance to this regulation permits the use of this adhesive in applications for which the adhesive either (1) is separated from the food by a functional barrier, which will prevent the migration of any of the adhesive components to the food, or (2) has incidental contact with food limited to the trace amount at the seams or the edges of the label.



This information is confidential, and restricted for the internal use of RSI México customers for informative purposes, and can not be reproduced or communicated to third parties without our written authorization.

TIJUANA: (664) 215.0679

PUEBLA: (222) 225.6594

HERMOSILLO: (662) 369.7306

comunicacion@rsimexico.com

