

PRESSIZA 24

PERFORMANCE GUIDE



Features

- Bright Gold Laminated Foil is an aluminum foil laminated to a white kraft base sheet, with an acrylic topcoating for printability
- Rubberbased adhesive featuring high initial tack and ultimate bond strength to a wide variety of substrates, including low surface energy plastics, treated glass, and corrugated cardboard
- Bleached supercalendered kraft stock featuring high internal strength, toughness, and tear resistance
- Used primarily for roll-to-roll label applications

Suggested applications

Good printing with solvent/waterbased Flexo. Not recommended for imprinting.

Face

Caliper 0.0037 +/- 10% inches

Adhesive

Thickness 1.0 mils
Peel Adhesion Glass PE treated: 2.34 lbs

Temperature Ranges

Minimum Application +25° F (-4°C)
Service Ranges -65° F to +160° F (-54°C to 71°C)

Liner

Caliper 0.0025 +/- 10% inches
Basis Weight 42 per ream +/- 10%
(24" x 36" 500 sheets)

Shelf Life

Unless specified otherwise in this document, one year when stored at 72°F at 50% RH

Important:

Suitable for applications where compliance with FDA 175.105 is required. This section covers applications where incidental contact between food and adhesive could occur.



This information is confidential, and restricted for the internal use of RSI México customers for informative purposes, and can not be reproduced or communicated to third parties without our written authorization.

TIJUANA: (664) 215.0679

PUEBLA: (222) 225.6594

HERMOSILLO: (662) 369.7306

comunicacion@rsimexico.com

