

### Features

- Ultra smooth thermal transfer coated facestock which provides premium barcode printing for high and medium speed printers
- Smudge resistance has been optimized for a coated paper, but caution is recommended with contact scanners
- Features excellent high speed/wide web converting characteristics
- Suitable for applications where compliance with FDA 175.105 is required
- Bleached, calendered kraft stock featuring high internal strength, toughness, and tear resistance
- Used primarily for roll-to-roll label applications

### Face

Caliper 0.0030 +/- 10% inches

### Adhesive

Thickness 1.0 mil

Peel Adhesion HDPE: 3.72 lbs

---

#### Temperature Ranges

Minimum Application +25° F (-4°C)

Service Ranges -65° F to +160° F (-54°C to +71°C)

### Liner

Caliper 0.0024 +/- 10% target

Basis Weight  
(24" x 36" 500 sheets) 39.1# per ream +/- 10%

#### Suggested applications

Rubber-based adhesive featuring high initial tack and ultimate bond strength to a wide variety of substrates, including low surface energy plastics, treated glass, and corrugated cardboard

#### Important:

The FSC® certification ensures that products come from well managed forests that provide environmental, social, and economic benefits. The FSC® chain of custody certification verifies that FSC® certified material is identified or kept segregated from non-certified or non-controlled material through this chain.

## Shelf Life

Unless specified otherwise in this document, ideally stored at 72°F at 50% RH



This information is confidential, and restricted for the internal use of RSI México customers for informative purposes, and can not be reproduced or communicated to third parties without our written authorization.

**TIJUANA:** (664) 215.0679

**PUEBLA:** (222) 225.6594

**HERMOSILLO:** (662) 369.7306

[comunicacion@rsimexico.com](mailto:comunicacion@rsimexico.com)

